

MONARFLEX WHITE MONOBOND JOINT AND LAP SEALANT



Commercial Product Data Sheet

Product Description

White Monobond is synthetic, cloth-based, joint and lap sealant double coated with an extremely aggressive adhesive. It is designed to offer superior adhesive strength over difficult substrate surfaces in a variety of exterior applications. Effective for wrapping or sealing joints and junctions. White Monobond is used where bonding to a difficult substrate is a concern, and where a standard cloth tape will not perform.

Product Benefits

- Produces an effective bond between adjoining or overlapping sheeting.
- Seals joints and junctions securely.

Quality Statements

Product is manufactured at an ISO 9001 - 2002 Certified facility.

Material Composition

Backing: synthetic cloth.

Adhesive: co-polymer pigmented, permanent type.

Liner: poly-silicone type sealant.

Measurements and Packaging

Thickness: 14 mil

Size: 2 ft x 75 ft roll

24 rolls per case; 75 ft per roll

Accessories

- Surface Cleaner: As recommended by sheeting manufacturer.
- Adhesive, Thinner, and Cleaner: As recommended by sheeting manufacturer.
- Sealant: As recommended by sheeting manufacturer.

Preparation Work

- Sheeting should be clean, dry, and free of oil, dust, and debris at overlap attachment sites.
- Clean and prepare scaffold sheeting to receive sealant tape.
- Do not apply components to surfaces unacceptable to manufacturer.

TECHNICAL DATA	
Property	
Thickness	14 mils
Color	White
Tensile Strength	27 lb/in (12.2 kg/25 mm)
Elongation	10%
Application Temperature	35°F to 120°F (2°C to 49°C)
Service Temperature	-30°F to 140°F (-35°C to 60°C)

Application

- Roll out materials to be taped to minimize wrinkles.
- Overlap edges and ends.
- Apply tape to bottom surface, remove release tape, set upper membrane flap on tape, and apply pressure with a roller to ensure seal.

Coverage

Each roll seals joints for 75 ft (22.8 m), 1800 linear feet (570 m) per case.

Limited Warranty

Siplast warrants this product to be free of defects in workmanship and materials only at the time of shipment from our factory. If any Siplast materials prove to contain manufacturing defects that substantially affect their performance, Siplast will, at its option, replace the materials or refund its purchase price.

This limited warranty is the only warranty extended by Siplast with respect to this material. There are no other warranties, including the implied warranties of merchantability and fitness for a particular purpose. Siplast specifically disclaims liability for any incidental, consequential, or other damages, including but not limited to, loss of profits or damages to a structure or its contents, arising under any theory of law whatsoever.

The dollar value of Siplast's liability and buyer's remedy under this limited warranty shall not exceed the purchase price of the Siplast material in question.

Rev 10/05



Exclusive North American Distributor

1000 E. Rochelle Blvd. • Irving, Texas 75062-3940 • 469-995-2200 • www.siplast.com

In Canada: 201 Bewicke Ave., Suite 210 • North Vancouver, BC V7M 3M7 • Toll Free 1-877-233-2338

Customer Service in North America: Toll Free 1-800-922-8800



An Icopal Group Company